


## HD26224

## 40-2500MHz Frequency Mixer

### Features

- LO/RF: 40-2500MHz
- IF: DC-1000MHz
- LO Level: +13dBm
- Conversion Loss: 8.0dB
- RF Input: Up to +9dBm
- IP3: +26dBm
- SMA Connector



### Description

HD26224 is a high IP3 passive double balanced mixer operates with LO drive level range of +10dBm to +16dBm.

### Electrical Specifications @ +25 °C, LO= +13dBm







Parameter	Unit	Minimum	Typical	Maximum
Frequency Range				
LO/RF	MHz	40		2500
IF	MHz	DC		1000
Conversion Loss	dB		8.0	9.0
LO-RF Isolation				
40-400 MHz	dB	32	47	
400-1250 MHz	dB	27	37	
1250-2500 MHz	dB	22	35	
LO-IF Isolation				
40-400 MHz	dB	28	38	
400-1250 MHz	dB	25	35	
1250-2500 MHz	dB	20	38	
RF Input Power up to	dBm		+9	
IP3 (Center Band)	dBm		+26	

**HD26224**

**40-2500MHz Frequency Mixer**

**Typical Performance @ +25 °C**

LO = +13dBm




## HD26224

## 40-2500MHz Frequency Mixer


### Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	+23dBm
Peak IF Current	40mA
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +100 °C

### Schematic



### Outline



	A	B	C	D	E	F	G	H
Inch	1.250	1.250	0.563	0.625	1.000	0.625	1.000	0.250
mm	31.75	31.75	14.29	15.88	25.40	15.88	25.40	6.35